Product Data Sheet

🖀 1-888-452-HANA (4262) 📮 info@hanawireless.com

🖂 9465 Southampton Pl, Boca Raton, FL 33434, USA



Model: HW2-N14-1V

14x12x7 Inch Weatherproof Enclosure with120 Vac Mounting Plate, Vent System



Features

- Molded Fiberglass Reinforced Polyester (FRP)
- Stainless steel quick-release latches with padlock hasps
- NEMA Type 3R, 3RX / IP24 rated, fully gasketed lid
- Integral mounting flange, mast mounting option
- Aluminum mounting plate with 120 Vac outlets, ventilation system, patented (US8014157) slotted accessory mounting design

Applications

- Remote wireless LAN Wi-Fi equipment installations
- Indoor and outdoor installations
- Rapid deployment and hotspot installations
- Harsh and corrosive environments
- Protection of equipment from theft and damage

Specifications

MaterialFRPColorTool Gray – RAL 7035Voltage Vac120Heater F° (C°)N/AHeat Temperature ON/OFF F° (C°)N/AFan Power WattN/AFan Temperature ON/OFF F° (C°)N/AMounting Plate Dimensions in (mm)12.7 (322) x 10.8 (274) x 0.1 (2.5)Mounting Plate MaterialAnodized AluminumWeight lb (kg)10.6 (4.8)Outside Dimensions, Max in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24Cable Feed1/2in Conduit Connector		
Voltage Vac120Heater F° (C°)N/AHeat Temperature ON/OFF F° (C°)N/AFan Power WattN/AFan Temperature ON/OFF F° (C°)N/AMounting Plate Dimensions in (mm)12.7 (322) x 10.8 (274) x 0.1 (2.5)Mounting Plate MaterialAnodized AluminumWeight lb (kg)10.6 (4.8)Outside Dimensions, Max in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Material	FRP
Heater $F^{\circ}(C^{\circ})$ N/AHeat Temperature ON/OFF $F^{\circ}(C^{\circ})$ N/AFan Power WattN/AFan Temperature ON/OFF $F^{\circ}(C^{\circ})$ N/AMounting Plate Dimensions in (mm)12.7 (322) x 10.8 (274) x 0.1 (2.5)Mounting Plate MaterialAnodized AluminumWeight lb (kg)10.6 (4.8)Outside Dimensions, Max in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Color	Tool Gray – RAL 7035
Heat Temperature ON/OFF F° (C°)N/AFan Power WattN/AFan Temperature ON/OFF F° (C°)N/AMounting Plate Dimensions in (mm)12.7 (322) x 10.8 (274) x 0.1 (2.5)Mounting Plate MaterialAnodized AluminumWeight lb (kg)10.6 (4.8)Outside Dimensions, Max in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Voltage Vac	120
Fan Power WattN/AFan Temperature ON/OFF F° (C°)N/AMounting Plate Dimensions in (mm)12.7 (322) x 10.8 (274) x 0.1 (2.5)Mounting Plate MaterialAnodized AluminumWeight lb (kg)10.6 (4.8)Outside Dimensions, Max in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Heater F° (C°)	N/A
Fan Temperature ON/OFF F° (C°)N/AMounting Plate Dimensions in (mm)12.7 (322) x 10.8 (274) x 0.1 (2.5)Mounting Plate MaterialAnodized AluminumWeight lb (kg)10.6 (4.8)Outside Dimensions, Max in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Heat Temperature ON/OFF F° (C°)	N/A
Mounting Plate Dimensions in (mm) 12.7 (322) x 10.8 (274) x 0.1 (2.5) Mounting Plate Material Anodized Aluminum Weight lb (kg) 10.6 (4.8) Outside Dimensions, Max in (mm) 15.5 (393) x 13.5 (342) x 8.7 (220) Inside Dimensions in (mm) 13.5 (343) x 11.5 (292) x 5.8 (147) Flame Rating UL 94-5V RoHS Compliant Environmental Rating NEMA - IP 3R, 3RX - 24	Fan Power Watt	N/A
Mounting Plate MaterialAnodized AluminumWeight lb (kg)10.6 (4.8)Outside Dimensions, Max in (mm)15.5 (393) x 13.5 (342) x 8.7 (220)Inside Dimensions in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Fan Temperature ON/OFF F° (C°)	N/A
Weight lb (kg) 10.6 (4.8) Outside Dimensions, Max in (mm) 15.5 (393) x 13.5 (342) x 8.7 (220) Inside Dimensions in (mm) 13.5 (343) x 11.5 (292) x 5.8 (147) Flame Rating UL 94-5V RoHS Compliant Environmental Rating NEMA - IP 3R, 3RX - 24	Mounting Plate Dimensions in (mm)	12.7 (322) x 10.8 (274) x 0.1 (2.5)
Outside Dimensions, Max in (mm) 15.5 (393) x 13.5 (342) x 8.7 (220) Inside Dimensions in (mm) 13.5 (343) x 11.5 (292) x 5.8 (147) Flame Rating UL 94-5V RoHS Compliant Environmental Rating NEMA - IP 3R, 3RX - 24	Mounting Plate Material	Anodized Aluminum
Inside Dimensions in (mm)13.5 (343) x 11.5 (292) x 5.8 (147)Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Weight lb (kg)	10.6 (4.8)
Flame RatingUL 94-5VRoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Outside Dimensions, Max in (mm)	15.5 (393) x 13.5 (342) x 8.7 (220)
RoHSCompliantEnvironmental Rating NEMA - IP3R, 3RX - 24	Inside Dimensions in (mm)	13.5 (343) x 11.5 (292) x 5.8 (147)
Environmental Rating NEMA - IP 3R, 3RX - 24	Flame Rating	UL 94-5V
•••	RoHS	Compliant
Cable Feed 1/2in Conduit Connector	Environmental Rating NEMA - IP	3R, 3RX - 24
	Cable Feed	1/2in Conduit Connector

Package Specifications

Package Quantity	1 per Carton
Length in (mm)	16.0 (406)
Width in (mm)	16.0 (406)
Depth in (mm)	16.0 (406)
Weight lb (kg)	11.1 (5.0)

Wireless That Works



